ER/WM&I DDT



000060622

Source/Driver: (Name & Number from ISP, IAG milestone, Mgmt. Action, Corres. Control, etc.)

Closure #: (Outgoing Correspondence Control #, if applicable)

Due Date

Control, etc.)

Annette L. Primrose
Originator Name

QA Approval

Alan M. Parker

Contractor Manager(s)

Chris Dayton

Kaiser-Hill Program Manager(s)

T. G. Hedahl

Kaiser-Hill Director

Document Subject:

KH00003NS1A

NOVEMBER 15, 1995 CLEANUP STANDARDS MEETING MINUTES - AMP-168-95

November 29, 1995

95-RM-ER-185-KH

Discussion and/or Comments:

Attached are the meeting minutes for the above meeting. If you have no questions, please transmit these to the Department of Energy/Rocky Flats Field Office. For corrections or concerns, please contact Annette Primrose at extension 4385.

cc:

L. M. Brooks - K-H
D. C. Shelton - K-H

F. W. Chromec - RMRS C. S. Evans - RMRS

R. Z. Houk - RMRS

J. E. Law - RMRS

A. M. Parker - RMRS
B. L. Roberts - RMRS

T. P. Lovseth - RMRS

A. L. Primrose - RMRS

ER Records Center (2) RMRS Records

22.015.F

COLA



DOCUMENT CLASSIFICATION REVIEW WAIVER PER CLASSIFICATION OFFICE

NOTES ON CLEANUP STANDARDS MEETING - NOVEMBER 15, 1995

The working group developing a site-wide groundwater strategy and cleanup standards for RFETS held its fifth meeting on November 15, 1995. The session was mediated by personnel from Keystone and twenty six people attended.

The following agenda was developed by Keystone:

- introductory remarks;
- information on Ryan's pit
- standards and action levels;
- assignment for the next meeting; and
- arrangement of the next meeting.

These items form the major headings of this summary.

A working sub-group (Judy Bruch, Chris Dayton, Bill Fraser, John Law, Jeb Love, Keith Motyl, and George Setlock) was previously assigned to work on the issue of surfacewater standards. The results from this subgroup are presented under the appropriate heading.

I. Introductory remarks

The minutes from the previous meeting were presented, and the Keystone mediators discussed the matrix of 25 tasks which must be completed before the Rocky Flats Cleanup Agreement (RFCA) can be finalized. Each task had been assigned to a working group consisting of one representative from each concerned party (EPA, Colorado, DOE, and Kaiser/Hill). The previously formed groundwater strategy group was tasked with determining a variety of cleanup standards according to the mediators. Before December 15th, 1995, this group must identify the cleanup standards to be applied, and must specify where and how the standards will be applied. December 11th is the deadline to allow results to feed into negotiations.

II. Information on Ryan's Pit

The working group requested additional information on the cleanup of Ryan's Pit during the previous meeting. Zeke Houk, Rocky Mountain Remediation Services (RMRS) Project Manager for the removal action, provided that information. Ryan's Pit is located southeast of the industrial area and south of the 903 Pad. It was named in honor of Ed Ryan, the manager of the paint shop, who used the pit to dispose of paint shop waste until its closure in 1972.

RMRS conducted a removal action last September to deal with the pit. The contaminated soil and waste generated in this removal action currently are sitting in covered roll-off boxes in OU-2 and will be thermally desorbed before it is returned to the pit. A

modification to the RCRA operating permit has recently been approved, and a thermal desorption unit will be brought onsite for the treatment. The pit currently is sitting open and fenced.

The removal action was performed with personnel under supplied air. Post-excavation confirmation samples were collected, following an approved sampling plan, once the excavation was completed. The sampling was performed in level D personnel protection following appropriate health and safety screening. All confirmation samples were below the soil removal levels proposed by the working group except those collected from a localized area near the south wall of the pit where drums of free-liquids were encountered during excavation. The confirmation samples from the south wall (samples 304 and 305) contained fairly high levels of VOCs. TCE is greater than the soil value calculated to protect groundwater at 100 times the MCL. Attachment 1 lists the preliminary results of the confirmation samples taken after remediation of the trench. These results have not been reviewed and are for discussion purposes only.

If the source removal levels proposed by the working group had been in place at the time of the Ryan's Pit removal action, the boundaries of the excavation would have been extended as one sample is above the proposed levels. In the future, field gas chromatograph will still be used to direct excavation, and remove contamination (within practical limits). While measures will be use to maximize the usefulness of source removal, excavation will continue to have limitations even with the best measures. There are limits to the practicality of excavating plumes in water saturated soils and in unstable soils.

III. Standards and Action Levels IIIA. Source Removal Standards

The working group deferred a decision on source removal levels during the last meeting pending a discussion of the cleanup of Ryan's Trench, and the moderator requested a decision on this point. EPA found the proposal acceptable with a change to state that excavation into the groundwater would be decided on a case-by-case basis.

The CDPHE finds point #5 of the proposal confusing and requested clarification. This clause was intended to apply to isolated detections of COCs above action levels which do not appear to contribute to groundwater contamination and which could not be excavated practically. The wording of the statement will be revised to better reflect this purpose.

The CDPHE commented that the soil-removal levels based on 100 times MCLs are planning levels which are simply the level required for source control. It is unclear how far the sources will be chased in the field, and where residual contamination remains, additional action may be required. Susan Evans of RMRS will re-write the proposal to reflect the consensus views, and this draft will be circulated for review by all parties.

IIIB. Groundwater Point of Compliance and Standards

DOE RFFO presented a proposal for specific actions to deal with groundwater contamination (Attachment 2). This proposal was in response to the CDPHE's

suggestion that additional flexibility might be available on the issues of points of compliance and compliance standards under certain conditions. The DOE proposal included a combination of source removals, additional source control actions (if necessary), and specific actions for the dilute, dissolved phase plumes impinging surface water. The CDPHE discussed possible problems with passive treatment systems. Such systems would have to be engineering for freezing weather and other site conditions.

CDPHE then stated that there was no additional flexibility on point of compliance and numerical standards but there is flexibility in how the point of compliance and numerical standards are applied. The standards, for example, could be applied either as RCRA requirements or as other standards, and it may be possible to use some term other than point of compliance for the issue.

The CDPHE suggested that groundwater standards equal surface water standards, and questioned the wisdom of capturing the distal portions of plumes near the streams. CDPHE stated that the most cost-effective measures for groundwater cleanup are those implemented near the source and felt that it is difficult and expensive to deal actively with dissolved phase plumes at some distance from the source.

The CDPHE suggested that the groundwater effort focus on the sources of contamination and proposed a possible two-tiered approach to compliance with action levels for near-term cleanup and long-term compliance levels. Full compliance with the standards would be a long-term goal, but areas exceeding some higher trigger level would be aggressively remediated. The trigger could be 100 time MCLs or some other standard, but there was resistance to the use of PPRGs in this way. The CDPHE also suggested that installing large slurry walls to deal with dissolved phase plumes would not be wise, and stated again that capture near the source is the best strategy.

The concept of triggers and point of compliance were developed further. Site-wide triggers are a possibility, and such triggers could mean a site-wide point of compliance. An exceedance of the trigger levels would set off an evaluation of possible actions (including source removal). Monitoring will probably be required for a number of years under any scheme, and it may take a number of years for the plumes to reach the final standards. Actions focused on the sources of the plumes, however, will allow plumes to attenuate without replenishment and will eventually be successful. There seemed to be a consensus that if a source removal action was taken, that the distal end of the plume could be allowed to naturally attenuate without additional action.

Groundwater compliance could be judged with a combination of compliance wells and evaluation (or early warning) wells. The compliance wells would be used to gauge the ultimate success of groundwater cleanup, and the early-warning wells would be used to gauge the advance or retreat of plumes. Wells for both purposes were suggested at the previous meeting by a working sub-group, and the working sub-group will reassemble to consider this issue in more detail (Chris Dayton, Kaiser-Hill, has the lead on this and the group will meet Monday morning, November 20 at Interlocken).

Groundwater standards should equal surface water standards, according to the CDPHE, but the standards to be used have not been determined definitively. A general analysis of pathways will be required to support any levels which are chosen to protect surface water. The Keystone staff captured the ideas advanced by the CDPHE during the meeting (Attachment 3).

IIIC. Surface Water Standards

The working sub-group on surface water standards presented results from the session. The sub-group made considerable progress but was deadlocked on the issue of radioactive COCs until the EPA offered a possible compromise. Radioactive contaminants remain contentious, but agreement was approached on non-radioactive COCs. RMRS presented a proposal for radioactive COCs to the full groundwater group (Attachment 4). The proposal included:

- the proposed MCL for plutonium of 0.62 pCi/l;
- a design goal for pond management of 0.05 pCi/l; and
- the 1x10⁻⁶ level for open-space use of 141 pCi/l.

The CDPHE expressed some concerns with these risk-based levels. The 1x10⁻⁶ residential risk-based level (stated to be approximately 0.15 pCi/l in the meeting) should apply to all water in the creeks. The warm-water ecological segment 2 standards and recreational exposure also apply in the creeks, but the issue of point of compliance for the creeks remains undecided.

The proposed MCL of 0.62 pCi/l for plutonium would be a TBC requirement under CERCLA, and the site meets this standard (with a considerable safety margin) now in the creeks and ponds. DOE contended that severe storms could cause these levels to be exceeded locally, but the streams would serve as backup settling zones under some circumstances. However, CDPHE contends that the vision for the outer buffer zone, clearly states that all reaches of the stream must be suitable for all uses, and that particulate-bound plutonium will not settle significantly in the stream.

The DOE suggested that the 0.62 pCi/l standard should apply to water moving offsite, but the CDPHE suggests that the vision precludes such levels at Indiana Street. The CDPHE did not have enough time to prepare a counter proposal, but notes that whatever proposal is developed most go through the CERCLA public involvement process. According to CDPHE, the Colorado Water Quality Control Commission has the authority to regulate radioactive constituents in effluent streams, but the three parties should reach consensus about what makes technical sense.

The CDPHE then led a discussion of possible risk-based standards in the stream. The possible risk-based standards to protect human health vary between 0.15 and 0.60 pCi/l, and the point of compliance should be in the stream. Drinking water standards may be restricted to the outer Buffer Zone, but the CDPHE suggests that much of the discussion of elevated plutonium was hypothetical because plutonium levels in these water bodies

have always been extremely low and will continue to be less than any proposed risk-based number.

There was further discussion about the terminal ponds as a point of compliance. DOE made it clear that there is no intent to negotiate these in order to allow for sloppiness in remediation or D&D. The DOE plans to manage the A and B series ponds in the long-term, and cleanup and regulation of the ponds for unrestricted use would not be justified.

IV. Other Actions

Concerning the other actions assigned to the cleanup standards group, EPA stated that it will be impossible for the working group to develop a surface water management plan by December, 15, 1995. The issue of no further action will also be conceptual and probably cannot be finalized. The best which can be hoped for is agreement on the basic issues and goals of surface water management and no further action. The issue of OU consolidation may be agreed on prior to the mid-December deadline. Kaiser-Hill mentioned that the water management and no further action issues are being handled by other working groups.

V. Assignments

The point-of-compliance working sub-group will reconvene to deal further with this issue. Susan Evans will re-write the proposal for standards for subsurface soils to be reviewed by all parties. The CDPHE will prepare a risk-based, counter proposal for the radioactive standard for surface water. Annette Primrose will prepare a draft of the group's consensus opinion for a two tiered approach to groundwater.

VI. Next Meeting

The next meeting will be Wednesday 22 November from 8:30 to 12:30 downtown in the EPA conference center.

Table 1. List of attendees


<u>Name</u>	<u>Organization</u>	Phone/Fax
Todd Barker	Keystone	534-7395/(970)262-0152
Ravi Batra	DOE	966-9664/966-7447
Laura Brooks	KH ER/WM&I	966-6130/966-6406
Norma Castaneda	DOE EP	966-4226/966-4871
Win Chromec	RMRS	966-4535/966-7193
Chris Dayton	KH ER/WM&I	966-9887/966-5001
Susan Evans	RMRS	966-3199/966-9173
Bill Fraser	EPA	312-6580
Tom Greengard	SAIC	273-1253/279-5525
Purna Halder	DOE	966-9718/966-4728
Zeke Houk	RMRS	966-3148
Gary Kleeman	EPA	312-6571/312-6897
John Law	RMRS	966-4842/966-2623
Jeb Love	CDPHE	692-3511/782-4969
Tim Lovseth	RMRS	966-8249/966-7193
Richard Marty	Jason Associates	430-1710/430-1906
Elizabeth Pottorff	CDPHE/WQCD	692-3586/782-0390
Annette Primrose	RMRS	966-4375/966-2623
Tim Rehder	EPA	312-7102/312-6897
Tim Reeves	SAIC	273-1250
Barry Roberts	RMRS	966-4530
Joe Schieffelin	CDPHE	692-3356/759-5355
Steve Slaten	DOE	966-4839/966-4728
Carl Spreng	CDPHE	692-3358/759/5355
Robert W. Terry	CDPHE/Rad Control	692-3051/782-5083
Susan Wilcox	Keystone	534-7395/(970)262-0152

Attachment 1. Information Concerning Ryan's Pit.

Attachment 2. Specific Groundwater Proposed Actions.

Attachment 3. Keystone synthesis of groundwater point of compliance issues

Attachment 4. Surface water proposal



RYANPIT2.XLS

Lab Location Analyte	Result C	Open Space PPRG 10-6		<i>P</i> r ≈ 100 X MCL	% of the PPRG	% of the MCLx100
A639901 N wall 11,1,1-TRICHLOROETHANE	i iU	. !	3.78	378		
A639901 N wall 1,1-DICHLOROETHENE	U	2.24	0.119			
A639901 N wall 1,2-DICHLOROETHANE	U	41701	0.063			
A639901 N wall 1,2-DICHLOROETHENE	U	11.11	0.095			
A639901 N wall CARBON TETRACHLORIDE	U					
A639901 N wall ETHYLBENZENE	U	856001	17.6	1760		
A639901 N wall METHYLENE CHLORIDE	· U	122!	:	01	·	
A639901 N wall TOLUENE	U	126000	20.4	2040;		
A639901 N wall TRICHLOROETHENE	U		0.0931	9.27!		
A639901 N wall XYLENE	U	17400001	2961	29600		• :
A640001 E wall 1,1,1-TRICHLOROETHANE	.U	:	3.78	378		
A640001 E wall 1,1-DICHLOROETHENE	U	2.24	0.119	11.9		
A640001 E wall 1,2-DICHLOROETHANE	U	4170!	0.0631	6.33!		
A640001 E wall 1,2-DICHLOROETHENE	U	11.1	0.095	9.51		
A640001 E wall CARBON TETRACHLORIDE	:U i	13.5	0.11	11:		
A640001 E wall CHLOROFORM	·U	197:	1.52	152:		
A640001 E wall ETHYLBENZENE	·U i	85600!	17.6	1760:		
A640001 E wall XYLENE	U	17400001	296	29600!	:	
A6401011S wall 1,1,1-TRICHLOROETHANE	IU :	i	3.78	378		
A640101 S wall 1,1-DICHLOROETHENE	·U	2.24	0.119	11.91		
A640101 S wall 1,2-DICHLOROETHANE	iU	4170	0.0631	6.331	;	
A640101 S wall 1,2-DICHLOROETHENE	U	11.1	0.0951	9.511	:	
A640101 S Wall CARBON TETRACHLORIDE	U	13.5	0.11			
A640101 S wall METHYLENE CHLORIDE	IU I	122		0		
A640101 S wall TETRACHLOROETHENE	U	35.2	0.115	11.5	!	
A640101 S wall TOLUENE	U	126000	20.4	2040	i	
A640101 S wall XYLENE	ĮU į	1740000	2961	296001		
A640201 W wall 1,2-DICHLOROETHENE	ĮU ,	11.1	0.095	9.51		
A640201 W wall CARBON TETRACHLORIDE	!U	13.51	0.11	111		
A640201 W wall CHLOROFORM	U	197	1.52	1521		
A640201 W wall ETHYLBENZENE	U	856001	17.6	17601		
A640201 W wall METHYLENE CHLORIDE	U	122		01		
A640201 W wall TETRACHLOROETHENE	:U :	35.2	0.115	11.5i	:	
A640201 W wall TOLUENE	:∪ :	1260001	20.41	2040		
A640201 W wall XYLENE	·U	17400001	296	29600i		
A640301 SW floor 11,1-DICHLOROETHENE	U	2.24	0.119!	11.9i		
A640301 SW floor 11,2-DICHLOROETHANE	U ·	4170i (0.0631	6.33		
A640301 SW floor 1,2-DICHLOROETHENE	:U '	11.1! (0.095	9.51!		
A640301 SW floor CARBON TETRACHLORIDE	U	13.5	0.11	11!		
A640301 SW floor CHLOROFORM	U ,	197!	1.52!	152!		
A640301 SW floor METHYLENE CHLORIDE	U	122!	:	01		
A640301 SW floor TRICHLOROETHENE	,U :	134! (9.27!		
A640301 SW floor XYLENE	U	17400001	296	29600!		
A640401 NW floor 1,1-DICHLOROETHENE	U :	2.24 (11.91		
A640401 NW floor: 1,2-DICHLOROETHENE	U	11.11 (9.514		
A640401 NW floor CARBON TETRACHLORIDE	U		0.111	111		
A640401 NW floor CHLOROFORM	· · ·		1.521	152!		
A640401 NW floor ETHYLBENZENE	·U	856001	17.6i	17601		
A640401 NW floor METHYLENE CHLORIDE	U	122		10		
A640401 NW floor TOLUENE	U '	1260001	20.4!	2040		
A640401 NW floor XYLENE	·U	1740000:	2961	29600:		

RYANPIT2.XLS

			Open :				
Lab number Location Analy	te	Result C		MCL	100 X MCL	% of the PPRG	% of the MCLx100
A640501 NE floor 1,1,1-TRICHLOR	OETHANE	U	1 .	3.781	3781		.:
A640501 NE floor 11,1-DICHLOROE		·U	2.241	0.119	11.91		
A640501 NE floor 1,2-DICHLOROE		U	41701	0.063	6.331		
A640501 NE floor 1,2-DICHLOROE	THENE	Ü	11.11	0.095	9.51		
A640501 NE floor ACETONE		U	25600!		0!		
A640501 NE floor CARBON TETRA	CHLORIDE	U	13.5	0.11:	11:		
A640501 NE floor CHLOROFORM		;U	197:	1.52!	152i		
A640501 NE floor ETHYLBENZENE		U	85600	17.61	1760:		
A640501 INE floor METHYLENE CH		U	122		Oi		-
A640601 SE floor 1,1,1-TRICHLORG		U		3.78;	378		
A640601 SE floor 1,1-DICHLOROE		U	2.24: (0.1191	11.91		
A640601 SE floor 1,2-DICHLOROE	THENE	U	11.11 (0.0951	9.51		
A640601 SE floor ACETONE		·U	25600	1	Oi		
A640601 SE floor CARBON TETRA	CHLORIDE :	, įU	13.5	0.11;	11:		
A640601 SE floor CHLOROFORM		:U	197	1.52	152		
A640601 SE floor TOLUENE	!	U	126000	20.41	2040		
A640601 SE floor TRICHLOROETH	ENE	U	134: (0.093	9.27		
A640601 SE floor IXYLENE		:U :	1740000!	296i	296001		
A640701 NW wall 1,1,1-TRICHLORG		iU	!	3.78	3781		
A640701 NW wall 1,1-DICHLOROET		U	2.241 0	0.119	11.91		
A640701 NW wall 1,2-DICHLOROET	HANE	'U [41701 0	0.063	6.331	į	
A640701 NW wall ETHYLBENZENE		!U	85600	17.6	1760!		
A640701 NW Wall METHYLENE CHI			122				
A640701 NW wall TETRACHLOROE	THENE	ĮU	35.2 0	115	11.5		
A640701 NW wall TOLUENE		U	126000	20.4	2040		
A640701 NW wall TRICHLOROETHE		iU	1341 0	0.093	9.27		
A640801 SW wall 1,1-DICHLOROET	HENE	U	2.24: 0	0.1191	11.91		
A640801 SW wall 1,2-DICHLOROET		U i	41701 0	.0631	6.331		
A640801 SW wall 1,2-DICHLOROET	HENE	[U	11.1! 0	.0951	9.511		
A640801 SW wall ACETONE	and the same of th	0.002 BJ	256001	<u>i</u>	i	0%.	
A640801 SW wall ACETONE	i	0.003 BJ	25600!			0%:	
A640801 SW wall CARBON TETRAC	HLORIDE	<u> U </u>	13.51	0.111	111		
A640801 SW wall CHLOROFORM	<u> </u>	U !		1.52!	1521		
A640801 SW wall TETRACHLOROE		0.002!J	35.2! 0		11.5	0%	0%
A640801 SW wall TETRACHLOROE	THENE	0.003IJ	35.2! 0	.115	11.5	0%:	0%
A640801 SW wall TRICHLOROETHE		0.002!J	134: 0	.0931	9.27	0%.	0%
A640801 SW wall TRICHLOROETHE		0.003IJ	1341 0		9.27	0%	0%
A643103 NW floor 1,1,1-TRICHLORO		0.004IJ		3.781	3781		0%
A643103 NW floor 1,1,1-TRICHLORO		0.007 J		3.781	3781		0%
A643103 NW floor 1,2-DICHLOROET	HANE	0.005iJ	4170! 0.	.0631	6.331	0%	0%
A643103 NW floor ACETONE		0.004 BJ	25600		01	0%	
A643103 NW floor ACETONE	:	0.02818	256001		01	0%	
A643103INW floor TETRACHLOROE		0.013i	35.2! 0.		11.5i	0%:	0%
A643103INW floor ITETRACHLOROE		0.0141	35.2! 0.		11.51	0%,	0%
A643103 NW floor TETRACHLOROE		0.0191	35.21 0.		11.51-	0%;	0%
A643103 NW floor TRICHLOROETHE		0.004IJ	134! 0.		9.271	0%;	0%
A643103 NW floor TRICHLOROETHE		0.009IJ	1341 0.		9.27!	0%;	0%
A643304 S wall 1,1,1-TRICHLORO		0.12!J		3.781	3781		2%
A643304 S wall 1,1,1-TRICHLORO	CIMANE	813		3.781	3781	0%!	2.0
A643304 S wall ACETONE		0.3!BJ	256001		01	0%;	
A6433041S wall ACETONE	1	4 J	256001		01	0701	

RYANPIT2.XLS

Lab number	Location	Analyte	Result ppm	С	Open Space PPRG 10-6	MCL	100 X MCL	% of the PPRG	% of the MCLx100
A6433041	S wall	ACETONE	5.8	В	256001		0:	0%;	
A643304	S wall	CHLOROFORM	0.06		197!	1.52	152	0%:	0%
A6433041	S wall	ETHYLBENZENE	0.072	J	856001	17.6	1760!	0%	0%
A643304	S wall	TETRACHLOROETHENE	1.2		35.2!	0.115	11.5	3%,	10%
A643304	S wall	TOLUENE	0.23	J	1260001	20.41	20401	0%:	0%
A643304	S wall	TRICHLOROETHENE	0.098	J	134!	0.0931	9.27	0%:	1%
A643304	S wall	TRICHLOROETHENE	1:	J	1341	0.093	9.27!	1%:	11%
A643304	S wall	TRICHLOROETHENE	4:	J	1341	0.093	9.27	3%:	43%
A643304	S wall	XYLENE	0.4	J	17400001	296;	296001	0%:	0%
A643305	S wall	ACETONE	11	JB	256001	i	0	0%1	
A6433051	S wall	ETHYLBENZENE	15		85600	17.6	1760	0%:	1%
A643305	S wall	ETHYLBENZENE	27	!	85600	17.6	17601	0%1	2%
A643305	S wail	ETHYLBENZENE	28		85600	17.6	17601	0%.	2%
A643305	S wall	TETRACHLOROETHENE	110		35.2	0.115	11.5	313%	957%
A643305	S wall	TETRACHLOROETHENE	220		35.21	0.115	11.5	625%:	1913%
A643305	S wall	TETRACHLOROETHENE	250		35.2	0,115	11.5	710%	2174%
A643305i	S wall	TOLUENE	19		1260001	20.4	20401	0%:	1%
A643305	S wall	TOLUENE	100		126000	20.4	2040	0%;	5%
A643305	S wall	TRICHLOROETHENE	19	ĺ	134!	0.093	9.27	14%	205%
A643305	S wall	XYLENE	130		17400001	2961	29600	0%	0%
A643305	S wall	XYLENE	140		1740000	296	29600	0%	0%
A643305	S wall	XYLENE	220	į	17400001	296	296001	0%	1%

Proposed Groundwater Remediation

Goal: to protect surface water through a combination of source removals with a few, low-cost other remedial actions

Assumptions

- VOCs are the primary concern in groundwater
- Only passive treatment of dissolved phase contamination will be considered
- Hydrologic capture of VOC contaminated groundwater will be to the stream base

Source Removals Currently Planned

Funded: Trench T-2 Done Trench T-3 1996 Trench T-4 1996

IHSS 118.1-Carbon Tetrachloride Spill 1996 (Free phase recovery installed)

As Funding is Available:

903 Pad

Mound

IHSS 119.1 (OU 1)

Containment will be evaluated where the potential to impact surface water exists after the source removals are completed when:

- after source removals, residuals approach 100 times MCLs subsurface soil concentrations,
- there is no decreasing downgradient trend in groundwater concentrations over two years,
- where pathway evaluation still indicates a threat to surface water.

Discussion of Proposed Actions for Plumes

The focus is on areas where there is an impact on surface water, i.e. where surface water PPRGs are exceeded.

Plume assumed to be derived from the Carbon Tetrachloride Spill (IHSS 118.1)

- containment by barriers will be evaluated
- further excavation will be performed if required
- above will be based on the results of characterization planned for this year

Mound Plume where surface water PPRGs are exceeded in Walnut Creek

- spring boxes or similar methodology to capture seepage prior to entering creek
- passive treatment of water

Ryan's Pit where surface water PPRGs are exceeded downgradient of the trench

- spring boxes or similar methodology to capture seepage prior to entering creek
- passive treatment of water
- requires hydrogeologic data assessment to establish suitability and practicability

Seeps directly upgradient of Pond B-1

- spring boxes or similar methodology to capture seepage prior to entering creek
- passive treatment of water
- requires hydrogeologic data assessment to establish suitability and practicability

MEMORANDUM

To:

Action Levels Task Group and Support Staff

From:

Todd Barker and Sarah Walen, The Keystone Center

Subject:

Summary of key points from the November 14, 1995 Surface Water Meeting

Date:

November 15, 1995

As you are aware, a subset of the Action Levels Task Group met to discuss issues specific to surface water on Tuesday, November 14, 1995. A summary of key issues from that discussion is provided below.

Representatives from Rocky Flats presented a proposal for surface water that included surface water cleanup standards and points of compliance for surface water. Key aspects of the proposals are summarized in the following recommendations:

- Consistent with the Site Vision, waters of the site should not be classified as water supply.
- Points of compliance for surface water should be outlets of terminal ponds.
- Aquatic life Warm water 2, Recreational 2
- DOE regulates radionuclides
- Site discharge standard for Pu should be 141 pCi/l.
- Standard Pond Operation should be flow-through.

The group asked questions of clarification about the proposal and discussed the various aspects of the proposal in detail. Representatives of the State said they were particularly concerned about the process for managing the affected watershed area and identifying surface water standards. Critical to their concerns were the scientific basis for the method used and the standards selected. Based on experience, representatives of the State believe that they can provide Rocky Flats with a defensible scientific process of watershed analysis to establish appropriate surface water action level standards.

• At the close of the November 15 meeting, the group will meet to determine the need for an additional meeting to discuss surface water action levels and points of compliance.

248\01\AL-003.SKW

DOE / K-H / RMRS WORKING GROUP PROPOSAL November 15, 1995

Radionuclides

- Action level for 0.62 pCi/liter is at Indiana Street and is a 30-day running average.
 Exceedance triggers notification and reporting to DOE, EPA, CDPHE, and the Cities.

 Letter report due within _____ days and will follow NPDES notification guidance.
- Design goal for pond management is 0.05 pCi/liter.
- Internal treatment systems may have other design goals.
- · Agreed upon minimum monitoring network.
- At 141 pCi/l we have Remediation Action Level (based on 10-6 risk) and Notification.

Non-Radionuclides (orgs--VOAs, etc.-- & metals & inorganics--NH₃)

- Like radionuclides, assumes existing stream standards are risk-based.
- Measurement point is at terminal ponds through completion of remediation / ASAP.
- After ASAP thalweg of stream is Point of Compliance.
- Classified uses are Aquatic Life, Warm Water, Recreation Class 2, and Agricultural.
 - Consequences per current regulations.